



# PRODUCT DATA SHEET

LC-E113

Single Component Core/Edge Fill

### Description

LC-E113 is a single component, 250°F (121°C) curing paste adhesive designed for creating structural hard spots within honeycomb sandwich structures as well as edge close out.

### Advantages

LC-E113 is a low sag adhesive with excellent adhesion to both facing and core material allowing the sandwich structure and edge close out to be performed in a single operation where applicable. LC-E113 can be easily applied with trowel or spatula.

### Physical Properties & Mix Ratio

Density: 90 lbs/cf

Color: Off white

### Available Packaging

1 gallon (10 lbs.) (LC-E113/1)

5 gallon (50 lbs.) (LC-E113/5)

Other packaging available upon request

### Work/Shelf Life

Work Life at Room Temperature: 70° F (21° C): 4 days (300 grams mass)

Shelf Life @ 40° F (4.4° C): 6 Months

**CAUTION: WHEN USING QUANTITIES IN EXCESS OF 300 GRAMS, USE CAUTION AS LARGER QUANTITIES CAN CAUSE AN INCREASED EXOTHERMIC (IE. VERY HOT) REACTION. THE USER IS ENCOURAGED TO DEVELOP STANDARD PRACTICES.**

### Cure Cycle Recommendations

60 Minutes @ 250°F (121°C)

Mechanical Properties				
Property	Tested per Specification	-67° F	70° F	160° F
Compression Strength (psi)	ASTM D695	N/A	21,000	N/A
Lap Shear (psi)	ASTM D1002-10	N/A	2800	2900

\*Tests performed using 2024-T3 aluminum, press cured @ at 250°F (121°C).

LincolnCompositeMaterials.com

(714) 898-8350 Sales@LCMaterials.com

15422 Electronic Lane

Huntington Beach, CA 92649

Seller cannot anticipate all conditions under which seller's products, or the products of other manufacturers in combination with seller's products, may be used. Seller accepts no responsibility for results obtained by the application of seller's products or the safety and suitability of seller's products, either alone or in combination with other products. Users are advised to conduct their own tests to determine the safety and suitability of each such product or product combination for their own purposes. Unless otherwise agreed in writing, seller delivers the products without warranty of any nature, stated or implied, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of said products, whether used alone or in combination with other products. Purchaser waives any claim against seller for direct, indirect, consequential or exemplary damages against seller, including without limitation, damage which may incur as a result of purchaser's use or misuse of the product or the product's failure to conform to any particular specification.

REV 170911